

# SysLOCATE

## Triumph™ Specifications

### Physical Specs

Size:	5.1" x 2.1" x 1" (130 x 53 x 25mm)
Weight:	0.34lbs. (153g)

### GPS Specs

Receiver:	L1 Frequency (1575.42 MHz) 12 channel, continuous tracking receiver
Antenna:	External

### Environmental Specs

Temperature	
Operating:	-30 to +70C
Storage:	-40 to +85C

### Wireless Specs

Wireless:	Dual band 850/1900Mhz, North America GSM bands
Regulatory Approvals:	FCC / IC, PTCRB, AT&T

### General Specs

Input Voltage:	11.5 – 18.5 volts DC (12 volts DC is nominal) <> 2 pin 60v max
Power consumption:	30 mA when stopped 250 mA max when battery charging
Battery	Internal, Battery life up to 8 hours. Charge time: 60 minutes. Recharges automatically when power is replaced to unit.
Cellular Antenna:	Internal

### Installation LEDs

Color	No light	Solid	Blinking
<b>Red (Power)</b>	<b>No external power</b>	<b>Low voltage</b>	<b>OK</b>
<b>Green (Cell)</b>	<b>No cellular coverage</b>	<b>Searching for cellular signal</b>	<b>OK</b>
<b>Blue (GPS)</b>	<b>No GPS fix</b>	<b>Searching for GPS</b>	<b>OK</b>
<b>All LEDs blink in sequence when OK</b>			
<b>All LEDs blink together when locating</b>			
<b>All LEDs turn off for 15 seconds when sleeping</b>			

SysLOCATE  
11120 Roselle Street, Suite A  
San Diego, CA 92121

